

METERING PUMP ACCESSORIES

...Because We All Live Downstream

ECO VALVE Back Pressure/Pressure Relief

DESIGNED TO ENHANCE THE **ACCURACY** AND **SAFETY** OF YOUR METERING PUMPS.

- Range of 15-350 PSIG
- Optional gauge port in either direction
- PVC, CPVC, PP, PVDF and 316L S/S
- Sizes from 1/4" to 4" (DN 8 - 100)
- Higher temperature & pressure models available



CLEARVIEW Calibration Cylinders

DESIGNED TO ENSURE THE ACCURACY OF YOUR METERING PUMP.

Glass

PVC



- PVC, polypropylene
- Maintenance friendly Glass
- Translucent, chemical resistant, and break resistant
- Float level indicator
- Threaded, socket, flanged
- Standard sizes 100 ml to 20,000 ml
- **Other materials available upon request.**

PFS Injection Quills F X M Connection

- Provides for a more homogeneous mix in the pipeline
- Built-in checks to prevent back siphoning
- 2 sizes: 3" or 5" insertion length
- PVC, CPVC, PVDF, polypropylene, 316L stainless & Hastelloy C
- Pressure to 3000 PSIG
- Field repairable
- **Custom built in other sizes and materials.**



DESIGNED TO INJECT CHEMICAL INTO THE CENTER STREAM OF PROCESS.

CS Corporation Stops

DESIGNED TO INJECT CHEMICAL INTO THE CENTER STREAM OF PROCESS.



- Isolation valve allows for ease of maintenance
- Available in 7 materials of construction
- Sizes available 1/2" (DN15) to 3" (DN75)
- Connection in NPT, socket, or flanged
- **Custom built in other sizes & materials.**

ACCU-VENT

DESIGNED TO AUTOMATICALLY VENT GASES AND VAPORS.

- Vents gases and vapors released from Sulfuric Acid, Sodium Hypochlorite, & Hydrogen Peroxide
- Standard 1/2" or 3/4" NPT threaded connections, or socket weld
- **NEW!** Stainless Steel Accu-Vent for chemical, temperature, and pressure applications
- **NEW!** Compact Accu-Vent with 1/4" connection



ACCU-PULSE

Pulsation Dampeners

REMOVES PULSATING FLOWS FROM POSITIVE DISPLACEMENT PUMPS.



- Protect pipes, meters, valves and instrumentation from pulsation and vibration
- Decrease maintenance and costs
- Ensure meter accuracy, longevity and repeatability
- Prevent foaming and splashing
- Extensive range of materials and sizes



PRIMARY FLUID SYSTEMS INC.

For more information on our products, including literature and dimensional drawings, please visit our website:

www.ecovalve.com.cn

E-Mail: ecovalve@ecovalve.ca

Call Toll Free 1-866-324-6422

Fax (905) 333-8746

Optimizing Metering Pump Application Accessories Saves Money

By David Walker, General Manager, Primary Fluid Systems Inc.

During these times of economic constraint and increasingly stringent environmental and occupational health and safety regulations, it becomes imperative that applications requiring the dispensing and metering of expensive and hazardous chemicals be accomplished with the utmost accuracy, care and control.

For typical applications, when excess chemical is dispensed into the service, the addition of another chemical is required to offset this action, which results in increased expense. Conversely, if enough chemical is not dispensed into the process, the batch may be unsatisfactory for use and discarded and the processing repeated at further expense. Environmental and safety concerns are also important considerations.

The following is a general outline covering typical metering pump applications, as well as the accessory items that have been developed to enhance the performance of your metering pump.

Electronic & Motor Driven Metering Pumps

Whether diaphragm or piston style, these pumps generally incorporate check valves as the mechanical source to isolate the flow of the chemical, at each stroke of the diaphragm or piston. The response time of the check valve assemblies, enabling them to reseal at the end and beginning of each stroke is essential to the performance and continuous accuracy of the metering pump.

Back Pressure Control Valves

Many metering pump applications dispense to atmospheric conditions or into a process with less than 20 psig pressure and more typically, into a process with erratic system pressure. These applications require back pressure to ensure a constant pressure for the discharge check assembly on the metering pump to work properly.

It is crucial that a back pressure control valve such as **ECO VALVE** be installed in the discharge piping of the pump to ensure a constant pressure for the discharge check assembly to work under. This allows for the repeatability of a constant fluid discharge per stroke, and ensures the desired accuracy.

ECO VALVE back pressure valves automatically provide *anti-siphon* protection and are available in a wide range of sizes and materials of construction.

Calibration of Metering Pumps

Typically, metering pumps are used without proper calibration. The manufacturer provides a performance curve detailing the general discharge capacities of the pump. These curves are normally derived under controlled conditions, using water as the testing fluid. Given the large variety of chemicals available, with varying viscosities and specific gravities, and the wide differences in suction conditions on the pump and discharge piping, it is only reasonable that each application needs to be calibrated individually. Calibration must be repeated from time to time due to wear and vibration in the system.

CLEARVIEW calibration cylinders are available in PVC, polypropylene and glass construction in standard sizes from 100 ml to 20,000 ml. They provide an excellent way to periodically check the performance and accuracy of your metering pump.

Pulsation Dampeners

Pulsation is another typical problem with most metering pumps, and in some cases cannot be tolerated by the application. **ACCU-PULSE** pulsation dampeners are available in a variety of sizes and material for such situations and help remove a high degree of pulsing and surging in the line. They only work if installed properly, in the right order in the line, and with the right pressure bladder to offset the incoming pulsing. It is important that the directions supplied by the manufacturer regarding recommended set pressure and location of the dampener be adhered to.

Inline Pressure Relief Valves

When using motor driven pumps or solenoid pumps capable of higher pressures than your line is designed for (i.e. 150 psig), an inline pressure relief valve such as **ECO VALVE** must be installed to protect the line from overpressure and possible splitting which could cause uncontrolled discharge of hazardous chemical into the area.

Always install the pressure relief valve in the line closest to the discharge of the pump and ensure that there are no isolation valves or components capable of closing the discharge line off prior to the relief valve.

ECO VALVE pressure relief valves are available in a wide range of materials and sizes with adjustable pressure settings.

Safe Line Maintenance

When installing a metering pump system, install as many unions in the line as possible to allow for ease of maintenance and repair of the various components used. This can easily be accomplished with the use of true union valves, which also serve the purpose of isolating valves.

When handling hazardous chemicals and indeed any chemicals, always remember to design your piping system with a way to drain off the chemical and vent any built up pressure before service begins. This will prevent most of the spillage and reduce potential hazard in the workplace. Tee off the discharge of the pump at the lowest point back to the tank or install an inline pressure relief valve such as **ECO VALVE** that has the ability of venting back to the feed tank or calibration cylinder when set at "0" psig.

Injection Valves


A check valve, normally spring loaded is used for the purpose of isolating your discharge chemical line from your process line. Most metering pump manufacturers supply a standard injection valve with their pump. This valve should be utilized and installed at the point of injection and have an isolation valve in close proximity. There are all types of injection valves available to accommodate the various requirements of injection needed, dependent on the process pipe line size and volume.

PFS Injection Quills ensure that the chemical is fully dispersed into the center of the process line and provide for a more homogenous mix in the pipeline. A built-in check helps prevent back siphoning.

Conclusion

Properly designed, installed and maintained metering pump applications should provide dependable and accurate service with minimal downtime. In order to minimize maintenance and system problems, and to optimize the efficient use of chemicals, a modest investment in the suggested accessories is recommended.

If you have any questions regarding application installation or applications that are a problem and/or continuous expense, please contact our office for some free and friendly consultation.



Distributed by: