

# ACCU-VENT

## Automatic Degassing Valves

### 2022 US Price List

#### Standard Features

- CPVC (Corzan) corrosion-resistant materials of construction on standard models
- Specially designed float material that automatically vents built-up gases on system start up and under working pressure
- Can be used on feed side or discharge side of pump (or both)
- Available in Stainless Steel for specific chemical, temperature, and pressure applications
- Also available in compact style, with ¼" connection

Model	Material	Bottom Connection	Top Connection	Max. Temp.	Max. Pressure	Price
<b>AV-25-CPVC</b>	CPVC	¼" NPT or BSP Thread	¼" Thread	180 F (82 C)	150 PSIG	\$ 125.00
<b>AV-50-CPVC</b>	CPVC	½" NPT or BSP Thread	½" Thread	180 F (82 C)	232 PSIG	\$ 200.00
<b>AV-50-CPVC-S</b>	CPVC	Socketweld	½" Thread	180 F (82 C)	232 PSIG	\$ 200.00
<b>AV-75-CPVC</b>	CPVC	¾" NPT or BSP Thread	½" Thread	180 F (82 C)	232 PSIG	\$ 200.00
<b>AV-75-CPVC-S</b>	CPVC	Socketweld	½" Thread	180 F (82 C)	232 PSIG	\$ 200.00
<b>AV-100-CPVC</b>	CPVC	1" NPT or BSP Thread	1" Thread	180 F (82 C)	232 PSIG	\$ 246.00
<b>AV-25-PVDF</b>	PVDF	¼" NPT or BSP Thread	¼" Thread	180 F (82 C)	150 PSIG	\$ 392.00
<b>AV-50-PVDF</b>	PVDF	½" NPT or BSP Thread	½" Thread	180 F (82 C)	232 PSIG	\$ 740.00
<b>AV-75-PVDF</b>	PVDF	¾" NPT or BSP Thread	½" Thread	180 F (82 C)	232 PSIG	\$ 869.00
<b>AV-50-316S/S</b>	316 S/S	½" NPT or BSP Thread	1" Thread	500 F (260 C)	250 PSIG	\$ 351.00
<b>AV-75-316S/S</b>	316 S/S	¾" NPT or BSP Thread	1" Thread	500 F (260 C)	250 PSIG	\$ 377.00
<b>AV-100-316S/S</b>	316 S/S	1" NPT or BSP Thread	1" Thread	500 F (260 C)	250 PSIG	\$ 417.00
<b>AV-150-316S/S</b>	316 S/S	1.5" NPT or BSP Thread	1.5" Thread	500 F (260 C)	250 PSIG	\$ 883.00
<b>AV-200-316S/S</b>	316 S/S	2" NPT or BSP Thread	2" Thread	500 F (260 C)	250 PSIG	\$1,026.00

Contact our office for more information on product availability and applications. Other materials available upon request.

## Typical Installation

The installation below is a typical installation example only. Consult your engineering department for the appropriate installation for your application or call the factory for advice.

**Example: System arrangement for solenoid driven (above 150 psig) or motor driven pumps with highly recommended flooded suction conditions.**

